EXPLORE E+ 1 PRO ELECTRIC BIKE

SPECS

HYBRID CYCLING TECHNOLOGY	
MOTOR	Giant SyncDrive Pro
CONTROLLER	Giant RideControl Ergo
DISPLAY	Giant RideDash EVO
BATTERY	Giant EnergyPak Smart 625, 36V Integrated Lithium-Ion
FRAME	
SIZES	S, M, L
COLOURS	Satin Rosewood
FRAME	ALUXX SL aluminium, Overdrive 1½ - 1⅛" head tube, integrated KS18 kickstand mount, compatible with fenders
FORK	SR Suntour NCX D AIR LO 63mm travel 15AH
SHOCK	N/A
COMPONENTS	
HANDLEBAR	Giant Connect XC Riser 31.8x690mm
STEM	Giant Contact
SEATPOST	Giant 30.9mm, 2-bolt Micro Adjustable, Forged Aluminium
SADDLE	Selle Royal Vivo Ergo Moderate Unisex
PEDALS	Aluminium Platform
DRIVETRAIN	
SHIFTERS	Shimano Deore
FRONT DERAILLEUR	Shimano Deore
REAR DERAILLEUR	Shimano Deore, 11-Speed, Shadow+
BRAKES	Shimano BR-MT410, hydraulic disc, 180mm
BRAKE LEVERS	Shimano BL-M4100, I-spec EV)
CASSETTE	Shimano CS-M5100, 11-42T, 11-Speed
CHAIN	KMC e.11 Sport, e-bike optimized
CRANKSET	Forged Alloy minimal Q-factor, 36/48T
BOTTOM BRACKET	N/A
WHEELS	
RIMS	Giant eX 2, Tubeless Ready, 700c Aluminium
HUBS	Giant eTracker, sealed cartridge bearings [F] 15mm Thru-Axle [R] 142x12 Thru-axle
SPOKES	Sapim E-Lite [r] Race [f], e-bike optimized
TYRES	Giant Crosscut Gravel 2, 700x45c (622x45), Tubeless Ready, Reflex (max tyre width possible: 47mm)
EXTRAS	Giant EnergyPak 6A Smart Charger, Giant EnergyPak Plus range extender compatible
ACCESSORIES	
LIGHTING	Axa BlueLine 50Lux Steady E6 frontAxa BlueLine Steady E6 rear

FEATURES

- Frame: ALUXX SL aluminium, Overdrive 1½ - 1⅛" head tube, integrated KS18 kickstand mount, compatible with fenders
- Fork: SR Suntour NCX D AIR LO 63mm travel 15AH
- Shifters: Shimano Deore
- Crankset: Forged Alloy minimal Q-factor, 36/48T
- Colours: Satin Rosewood

Price: €4,399

GEOMETRY

FRAME	S	M	L
Seat Tube Length (mm)	435	485	535
Seat Tube Angle	74.0°	73.0°	73.0°
Top Tube Length (mm)	570	590	610
Head Tube Length (mm)	125	140	155
Head Tube Angle	69.5°	69.5°	69.5°
Fork Rake (mm)	42	42	42
Trail (mm)	91.3	91.3	91.3
Wheelbase (mm)	1112	1121	1142
Chain Stay Length (mm)	455	455	455
Bottom Bracket Drop (mm)	60	60	60
Stack (mm)	605	619	633
Reach (mm)	385	400	416
Stand Over Height (mm)	745	775	808
Handlebar Width (mm)	690	690	690
Stem Length (mm)	60	70	80
Crank Length (mm)	170	170	170
Wheel Size	700C	700C	700C

All specifications listed are subject to change without notice.